

Adhesive

5206-300ML-LOCTITE - 5206-300ML-LOCTITE

<https://www.123bearing.ie/lubricant-adhesive/adhesive/adhesive/5206-300ml-loctite>

TITRE	Anaérobie
DESCRIPTION	Étanchéité plane, moyennement flexible
NOM	LOCTITE 5206
CONDITIONNEMENT	Cartouche 300 ml
COMMENTAIRE	
APPROBATION*	

📄 Description

LOCTITE® 5206 is a red, viscous, fluorescent dimethacrylate ester acrylic flange sealant. It seals close fitting joints between rigid metal faces and flanges. It provides resistance to low pressures immediately after assembly. It is used as a form-in-place gasket on rigid flanged connections, e.g. gearbox and engine casings, etc.

🌟 Avantages

Fluorescent
Provides resistance to low pressures immediately after assembly
Used as a form-in-place gasket
May be dispensed robotically with the appropriate LOCTITE product conditioning and dispensing systems

🌟 Caractéristiques

Dimethacrylate ester flange sealant. It seals close fitting joints between rigid metal faces and flanges having immediate resistance to low pressures.

PRODUCT FEATURES

Brand	LOCTITE
N° Ean13	5010266266992
Type	ETANCHEITE
Packaging	1

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE